











MODEL S4s



Designed for On-wall or flushed in (2pi) applications. Perhaps our most versatile speaker Can be used as surround, height or LCR. When used as a surround channel the S4s has uncommonly high sensitivity, power handling and low distortion making this the ideal choice for high end theaters. Featuring our proprietary DPC-Array controlling Mid/High frequencies, centered by our finest 28mm Beryllium dome and dual 28mm TPCD ultra-lightweight domes. This new tweeter/waveguide DPC-Array delivers amazing accuracy, smoothness, and directivity control to handle the critical vocal range and delicate treble. The S4s shares the same DPC-Array and benefits from our unique timbre matching technique as found in the entire S-Series range of speakers. Unparalleled dynamic range, low distortion and musical finesse. The Perlisten S4s continues the lineup of speakers that have the distinguished honor to be the world's first and only loudspeakers to be certified for THX Dominus - their highest rating.

TECHNICALSPECIFICATIONS



Impedance



BASIC

Dimensions (HxWxD) 405 x 240 x 185mm 15.9 x 9.5 x 7.3" **Weight** 9.5 kg (20.9 lbs.)

Available finishesPiano Gloss Black, White

TECHNICAL

Enclosure Alignment

3-way acoustic suspension

Driver complement

DCP-Array: 28mm Beryllium 28mm(2) Textreme TPCD Woofers: 180mm Textreme TPCD

Sensitivity (2pi)

88.8dB / 2.83v / 1.0m

Impedance

 4Ω nominal / 3.2Ω min

Response Linearity

80 - 20kHz +/-1.5dB window

Frequency Response (-10dB)

39 - 37kHz

Typical In Room bass extension

33Hz

Recommended Amplifier Power

50 - 300W RMS

SPL capability @1m (100-20kHz)

113.6dB peak

111dB peak <2% - 2nd, 3rd Harmonics

Certification

THX Dominus, THX Ultra







TPCDThin Ply Carbon Diaphragms

